
# Mila 80S New High Tech Series

! Heat - High Voltage - Peak- Protected Does Not Produce Frequency Interference

Marine grade downlight







## **Product Specifications**

**Power Consumption** : 6, 9, 12, 14 Watt

Standart Voltage Internal Driver : 24 VDC Protected 60 VDC

**Optional Driverless** : Current 18 V 300-1.500 ma

: Mid Power OR High Power Light Source Led

Dimmable : PWM, Voltage, Current

Luminous Flux

### **Optional**

Special Arrangements Can Be Made For Projects Including Different Sizes, Materials, Material Colors



**Optional** Main Light And Emergency

Second Color

Temp Control

Does Not Cause fire

Does Not Cause Voltage Limit

Frequency











Dimensions



: 1.000 -1.350-1.800-2.100 Lumens



89 mm 20 mm

60 mm

i **]** 2 mm

**Material Colors** 





And Other Ral Codes

Light Angle

These Dimensions Can Be **Changed Optionally** 

The Driver Is Protected In An Aluminum Housing

79 mm



ANTIQUE







Standart Connection



Area Of Application

IP 40 Interior

**IP 65 Exterior** 

#### **Optional Connection** o **+** Red



Emergency Black Second color

## Interior



Exterior



**Light Colors** 









Certifications

