Mila 30S New High Tech Series

! Heat - High Voltage - Peak- Protected Does Not Produce Frequency Interference Marine grade downlight



Optional Main Light And Emergency OR Second Color



Product Specifications

3000K

Red

Blue

Green

6500K

Does Not : 3.6,5, 7, 9 Watt **Power Consumption** Voltage Limit **Temp Control** Cause fire Standart Voltage Internal Driver : 24 VDC Protected 60 VDC : Current 3 OR 18 V 300 - 1.500 ma Dimensions 60v **Optional Driverless** 39 mm :Mid Power OR High Power Light Source Led 2 mm 7.5 mm : PWM, Voltage, Current Dimmable 12 mm 6.5 mm Luminous Flux : 500 - 1.000 -1.350 Lumens 22 mm 50 mm **Material Colors** Light Angle 29 mm 30-32 mm BLACK PLATED TITANIUM PLATED 316 L POLISHED The Driver Is Protected In These Dimensions Can Be STEIN And Other Ral Codes **Changed Optionally** An Aluminum Housing ANTIC WHITE PLATED 316 L SATINE Area Of Application **Standart Connection** Optional Connection •+ Red **IP 40 Interior IP 65 Exterior** Main Black + Red •+ Red Emergency 0 — Black • - Black Second color Exterior Interior **Light Colors** Certifications \land 🛆 🖾 IP40 or IP65 C E

Optional Special Arrangements Can Be Made For Projects Including Different Sizes, Materials, Material Colors